





MODEL	WIDTH "A"	STRUCK VOLUME	HEAPED VOLUME	WEIGHT
HB60	60"	10 1/4 FT³	15 3/4 FT³	810 LBS
HB66	66"	11 1/4 FT³	17 1/2 FT <sup>3</sup>	870 LBS
HB72	72"	12 3/8 FT³	19 FT³	915 LBS
HB78	78"	13 3/8 FT³	20 3/4 FT <sup>3</sup>	960 LBS
HB84	84"	14 3/8 FT³	22 1/2 FT <sup>3</sup>	1015 LBS

## **FEATURES**

5" BALL BEARINGS THAT ARE TRIPLE SEALED TO PROTECT FROM THE ELEMENTS.
2 CUTTING EDGES LEADING UP TO THE DRUM TO SHRED ANYTHING TRYING TO GET THROUGH.
6,700 IN/LB CHAR-LYNN HYDRAULIC MOTOR HOUSED INSIDE THE DRUM FOR ULTIMATE PROTECTION.

CAPABLE OF HANDELING 24GPM OF HYDRAULIC FLOW

ULTRA HARD CARBIDE CUTTER TEETH ON DRUM.

GET ADDITIONAL CONTROL FROM THE DIRECT-DRIVE AND POWERFUL MOTOR WHICH ONLY PROTRUDES 2.5" BEYOND THE SIDE PLATE.

CROSSOVER RELIEF VALVES TO HELP DAMPEN SHOCK TO THE HYDRAULIC SYSTEM.

COMPLETELY FABRICATED IN OUR FACILITY IN CLEAR LAKE MINNESOTA.

© CMP ATTACHMENTS, LLC SIGNATURE DATE:
--